Approved For Release 2000/09/14 : CIA-RDP89B00551R000100150010-956

PRE-FLIGHT CHECKLIST FOR PERSONAL EQUIPMENT SECTION

- 1. Pre-Breathing Room (T.O. Minus 2:20):
 - a. Orderliness
 - b. Security
 - LC. Utilities (Electricity Air Conditioning)
- 2. Ground Vehicle Check (T.O. Minue 2:20):
 - -a. Walk Around check
 - 16. Starting
 - On Board: Spare Pack (1) Facepiece (1) D-2, 425 psi (2) Cushions (2) Parachutes (2).
- 3. Aircraft Oxygen Check (T.O. Minus 2:20):
 - a. Position Seat Pack in cockpit
 - oxygen pressure 1800 to 2000 psi
 - C. Connect oxygen and check for flow
 - M. Check radio through seat pack
 - e. Check face piece heat on normal and by-pass
 - Arrange placement of seat belt, harness, seat pack leads
- 4. Pre-Breathing (T.O. Minus 2:00):
 - a. Oxygen manifold and reduction system "ON"
 - b. 150 psi connected to console
 - $c_{\,\star}\,$ Console check flow and pressure 2 to 3 mm Hg
 - d. Fit underwear to pilot
 - e. Check and fit helmet assembly to pilot
 - f. Connect face piece to console turn "ON"
 - g. Pre-breath pilot and note time "ON"
- 5. Check Personal Equipment:
 - a. Suit condition
 - b. Helmet
 - ic. Gloves

Enclosure 2 to SOP-0-1, Page 1

A-LBeitle 7-21 Ragulaton 400 P.S.I.

Approved For Release 2000/09/14: CIA-RDP89B00551R000100150010-3

- Ld. Boots
 - e. Parachute
- 2 Coveralls
- Face piece and carrier
- h. Store items in sequence of wear after check.
- Periodically insure pilot's oxygen supply adequacy and comfort

6, Clothing Pilot (T.O. Minue:30):

a; Fit Pilot's suit assembly plus coveralls. Check all zippers, lacings and general appearance.

- b. Drinking water
- Remove pilot from console (Time noted); connect to D-2 charged 425 psi
 - Ld. Escort pilot to vehicle and plane

7. At Aircraft (T.O. Minus:20):

- .a. Fit parachute and back pack to pilot
- 2b. General evaluation of all garments
- Pilot hook-up in aircraft: Seat pack hook-up; engage capstan and breathing supply hoses; engage flight face piece to "T" block; connect amphenol; connect "U" plug; oxygen "ON"; check flow and change face piece; shoulder harness and seat belt; face piece heat check; press to test and check inflation.
 - d. Recheck all items get pilots approval
 - Le. Technician and vehicle remain "on line" until aircraft departure.

8. Post Flight:

- Report to aircraft at "Switch Off" time.
- Assist pilot out of aircraft and remove headgear.
- Remove personal equipment from cockpit.
- M. Return pilot to operations.
- e. Assist in removing clothing.
- f. Clean and perform minute inspection of all equipment.
- . Report to de-briefing for pilot report.

25X1A